

Fast Drying PLUS Water- Based Gloss

Leyland Trade Fast Drying PLUS is a water-based trim paint with an improved flow, minimising brush marks, making it easier to achieve a smooth finish. Our best ever water-based formula has enhanced durability, is fast-drying, low odour and has long lasting whiteness.

Ideal for use with Leyland Trade Fast Drying PLUS Water-Based Undercoat.

Recommended uses

Interior ✓ Exterior ✓

Type of substrate

Wood and Metal. For further advice on other substrates contact Technical Advisory.

Colour availability

Brilliant White and thousands of additional colours are available via the Leyland tinting system.

Finish

Gloss

Volume solid

41,9%

Coverage

1 litre will cover approximately 10-12 square metres, depending on the nature and porosity of the surface. Strong or contrasting colours may require additional coats.

Drying time

Touch dry in 1-2 hours. Recoatable after 4-6 hours.

Transportation and storage

To avoid the risk of spillage, always store and transport in a secure upright position. PROTECT FROM FROST.

Film thickness

Wet: 91 µm
Dry: 38 µm

Preparation

All surfaces to be painted should be clean, dry and free from loose and flaking material. Prime bare wood with Leyland Trade Fast Drying PLUS Water-Based Undercoat. Prime all other bare surfaces with the appropriate Leyland Trade primer. Rub down previously painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Apply one full coat of Leyland Trade Fast Drying PLUS Water-Based Undercoat to correctly prepared and primed surfaces before application of Leyland Trade Fast Drying PLUS Water-Based Gloss. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory on 01924 354354 or visit www.leylandtrade.com

Application

Ensure good ventilation during application and drying. Stir well before use. Easy to apply by brush or roller. Avoid overspreading. Do not apply in temperatures below 10°C or externally when rain is imminent. For best results use a synthetic brush.

Cleaning

Remove as much product as possible from application equipment before cleaning. To maintain brushes, do not allow paint to dry out on bristles. Regularly wash in clean, cold soapy water throughout use. Following prolonged use, clean with Clean Spirit, Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

Warning

- Keep out of reach of children.
- Avoid contact with skin and eyes.
- Do not ingest.
- If medical advice is needed have container or label to hand.
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency.
- SDS available: www.leylandtrade.com or call 01924 354354