

## Ceiling Paint

A low reflecting emulsion designed for interior walls & ceilings. The matt finish hides imperfections, and the quick & easy spot repair is ideal for areas of critical lighting.

### Recommended uses

Interior ✓

Exterior ✗

### Type of substrate

Internal finish for all types of Interior walls and ceilings, both bare and previously painted, including plaster, plasterboard, concrete, dry lining, ceiling tiles and wallcoverings etc.

### Colour availability

Brilliant White 10L

### Finish

Matt

### Volume solid

26.51%

### Coverage

10 litre will cover approximately 130m<sup>2</sup> depending on the nature and porosity of the surface. When using more than one tin of a colour in the same room, intermix before use.

### Drying time

Touch dry in 1-2 hours.  
Recoat after 2-4 hours, under normal conditions.

### Transportation and storage

To avoid the risk of spillage, always store and transport in a secure upright position. PROTECT FROM FROST.

### Thinner

Clean water.

### Film thickness

Wet: 105µm  
Dry: 27µm

### Preparation

Ensure surface to be painted is sound, clean, dry and free from grease. Remove all loose and defective paint. Rub down previously painted surfaces with fine waterproof abrasive to provide a good key. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. Seal absorbent surfaces with a coat of Leyland Trade Ceiling Paint thinned up to 5-10% with clean water.

### Application

Stir well before use. Suitable for application by brush, roller or spray. Apply two full coats, allowing 2-4 hours between coats under normal conditions. Two coats are normally recommended for good film build and obliteration. On certain surfaces and with severely contrasting colour changes, a third coat may be necessary. For spray application, thin with clean water as required, using up to approximately half litre of water to 5 litres of paint. Do not apply when air or surface temperature is below 10°C. Conditions of high humidity can prolong the drying time.

### Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use in warm soapy water and rinse thoroughly. Some local authorities have special facilities for disposal of waste coatings. Do not empty product into drains or watercourses. Replace lid firmly.

### Warning

- Keep out of reach of children.
- Avoid contact with skin and eyes.
- Do not ingest.
- Do not breathe spray.  
Wear respiratory protection.
- If medical advice is needed have container or label to hand.
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency.
- SDS available: [www.leylandtrade.com](http://www.leylandtrade.com) or call 01924 354354